

Technical Data Sheet

Page 1 of 2

Properties:	<p>AKEMI® Texturing Spray is a high-quality, one-component paint with structure formation containing solvents. The product is characterized by the following properties:</p> <ul style="list-style-type: none">- fast-drying- very good formation of structure on rigid plastics- very good adhesion on rigid plastics (PUR, PS, PA, EPDM, ABS, GFK and PVC)- can be painted with most paints commercially available- weather-resistant, non-yellowing- high surface hardness, at the same time good elasticity- resistant to petrol and thawing salt as well as the car wash								
Application Area:	<p>AKEMI® Structure Spray is used for the optical embodiment of vehicle parts made of rigid plastics. It can be also used in the domestic sector and for hobby purposes.</p>								
Instructions for Use:	<ol style="list-style-type: none">1. The surface must be free of grease, wax and dirt. Residues of polishing products or other care products are to be removed with afin® Acryclean.2. If necessary (scratches, damages) grind the surface, optionally fill with AKEMI® Elastic Filler.3. Shake the spray can vigorously for some minutes before use.4. Cover parts or surfaces not to be treated.5. Apply several thin layers (at a spraying distance of approx. 25 cm and at intervals of approx. 5 minutes).6. Repainting can be made after a drying time of 10 – 20 minutes.								
Special Notes:	<ul style="list-style-type: none">- Use AKEMI® »Liquid Glove« in order to protect your hands.- Do not use at too high temperatures or in intense sunlight because the paint dries too quickly and does not run properly (formation of haze). 15-25° C is the best working temperature.- The product dries much better if it is applied in several thin coats instead of one thick layer only.- The spray nozzle does not have to be emptied of paint when your work is done.- Parts which have been sprayed by mistake can be cleaned with AKEMI® Universal Dilution (compatibility check first!).								
Technical Data:	<table><tr><td>Colour:</td><td>transparent, structure-forming</td></tr><tr><td>Density:</td><td>approx. 0.76 g/cm³</td></tr><tr><td>Drying:</td><td>can be painted after approx. 20 minutes completely dry after approx. 2 hours</td></tr><tr><td>Coverage:</td><td>approx. 0.5 m²/spray can</td></tr></table>	Colour:	transparent, structure-forming	Density:	approx. 0.76 g/cm ³	Drying:	can be painted after approx. 20 minutes completely dry after approx. 2 hours	Coverage:	approx. 0.5 m ² /spray can
Colour:	transparent, structure-forming								
Density:	approx. 0.76 g/cm ³								
Drying:	can be painted after approx. 20 minutes completely dry after approx. 2 hours								
Coverage:	approx. 0.5 m ² /spray can								
Storage:	<p>If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 36 months from production.</p>								
Health & Safety:	<p>Read Material Safety Data Sheet before handling or using this product.</p>								

TDS 07.19

Technical Data Sheet

Page 2 of 2

Important Notice:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.